

SEARGE



1/1



## PATENT ABSTRACTS OF JAPAN

(11)Publication number: 09080315

(43) Date of publication of application: 28.03.1997

(51)Int.CI.

G02B 21/06

(21)Application number: 07232362

(22)Date of filing: 11.09.1995

(71)Applicant:

YOKOGAWA ELECTRIC CORP

(72)Inventor:

**KOSUGI YASUHITO** 


ISOZAKI KATSUMI

## (54) NIPKOW DISK TYPE OPTICAL SCANNER DEVICE

## (57) Abstract:

PROBLEM TO BE SOLVED: To eliminate a scan irregularity and obtain an image pickup screen having no light and shade stripe by synchronizing the scan period of the scanner device with the image pickup period of an image

SOLUTION: The top surface of a Nipkow disk 20 is irradiated with incident light 1. A multipoint scan on a sample is made with the incident light 1 transmitted through a scan track by rotating this Nipkow disk 20. Incident light 1 passed through a pinhole for scan start point detection, on the other hand, is photodetected by a photodiode 21 each time the pinhole for scan start point detection passes over a photodiode. At this time, the output current from the photodiode 21 varies in a pulse shape, so this current variation is converted by a current-voltage converting circuit 22 into a voltage, which is inputted to a voltage comparing circuit 23. Consequently, a voltage pulse train having the same period as the scan period can be led out as an output. This pulse train is supplied as a trigger signal to the external image pickup device 25 to synchronize the optical scanner device and image pickup device 25 with each other.





LEGAL STATUS

[Date of request for examination]

17.02.1998

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

3019754

[Date of registration]

07.01.2000

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998 Japanese Patent Office

MENU

SEARCH

INDEX

DETAIL



The Japanese Patent Office is not responsible for any damages caused by the use of this translation.

- 1. This document has been translated by computer. So the translation may not reflect the original precisely.
- 2.\*\*\*\* shows the word which can not be translated.
- 3.In the drawings, any words are not translated.

## **CLAIMS**

[Claim(s)]

[Claim 1] The image of a sample is used for the confocal point microscope constituted possible [ an observation ] by image pck-up equipment. While it is the Nipkow-disk type light scanner equipment containing the optical scanner fraction equipped with the Nipkow disk and the pinhole for a scanning starting point detection corresponding to the starting point of a scanning truck is arranged on the above-mentioned Nipkow disk Nipkow-disk type light scanner equipment characterized by providing a means to carry out the photo electric translation of the transmitted light of the above-mentioned pinhole for a scanning starting point detection, and to generate the trigger signal for the above-mentioned image pck-up equipment, and enabling it to take a synchronization of a scanning interval and the image pck-up period of image pck-up equipment.

[Claim 2] Nipkow-disk type light scanner equipment according to claim 1 characterized by preparing the micro-lens array disk constituted so that it might be arranged at the incident-light side of the above-mentioned Nipkow disk, it might have the micro-lens array of the pinhole pattern of a Nipkow disk, and the same pattern and a condensing light of each micro lens of a micro-lens array might carry out incidence to the pinhole to which a Nipkow disk corresponds in the above-mentioned optical scanner fraction.

[Translation done.]

2000/06/04	USPAT (	4 and 13	90	L14	BRS	15
06/	USPAT	7 and 14	0	L15	BRS	14
)6/	USPAT (	1 and 12	1332	L13	BRS	13
_	USPAT (	8 and 9	8366	L12	BRS	12
06/	USPAT 2	1 and 4 and 7	0	L11	BRS	<del>Г.,</del>
)6/	USPAT (	1 same 4 same 7	0	L10	BRS	10
)6/	USPAT 2	scanner	44073	Ь9	BRS	9
)6/	USPAT 2	camera	84909	Г8	BRS	∞
000/06/04 07:57	USPAT 2	5 adj 6	480	L7	BRS	7
)6/	USPAT 2	period	776557	L6	BRS	0
)6/	USPAT 2	rotational	230455	L5	BRS	رن ا
)6/	USPAT 2	2 adj 3	21848	L4	BRS	4
000/06/04	USPAT 2	time	182032 4	L3	BRS	ω
6/	USPAT 2	exposure	225229	L2	BRS	2
6/	USPAT 2	comparator	110342	L1	BRS	
Time Stamp	DBs	.Search Text	Hits	L #	Туре	

0		2000/06/04 08:35	USPAT	1 and 8 and 9 and 21	17	L22	BRS	22
0		2000/06/04 08:35	USPAT	confocal	2035	L21	BRS	21
0		2000/06/04 08:21	USPAT	4 and 19	Φ	L20	BRS	20
0		2000/06/04 08:21	USPAT	16 17 18	304	L19	BRS	19
0		2000/06/04 08:21	USPAT	396/116	87	L18	BRS	18
0		2000/06/04 08:21	USPAT	396/24	92	L17	BRS	17
0		2000/06/04 08:20	USPAT	396/20	132	L16	BRS	16
	ch ti							
ors		Time Stamp	DBs	.Search Text	Hits	# #	Туре	
	ro	,						

ť

							_	
			1	+	DBs	Time Stamp   Comm	ents   E	Time Stamp   Comments   Error Definition
	Type	# 니	Hits	Search Teac	$\dashv$		-	
	BRS	17	2030	confocal	USPAT	2000/05/29 14:54		
					11CDDT	15/29		
2	BRS	1.2	56850	microscope				
~	BRS	L4	43983	scanner	r .	2000/05/29 14:55		
,					1	2000/05/29		
4	BRS	L5	107497	107497 photograph\$3	_			
					1	2000/05/29	••••••	
2	BRS	1.6	105071	105071 photograp\$3				
					ì	2000/05/29		
9	BRS	L7	145	3 and 4	USFAI			
					E f	2000/05/29		
7	BRS	Г3	485	1 adj 2	USFAI	14:57		
					***************************************			